

SECTION 1105.08 R-7 MIXED HOUSING (MEDIUM TO HIGH DENSITY)
RESIDENTIAL DISTRICT.

1105.08 SUBD. 1. PURPOSE.

The R-7 Mixed Housing (Medium to High Density) Residential District is intended to provide a district which allows for a full and complete range and intermixing of residential activities, and to accommodate development areas which existed prior to the establishment of this Ordinance.

1105.08 SUBD. 2. PERMITTED USES.

The following are permitted uses within an R-7 District.

1. Multiple-family units, including two-family dwellings.
2. Public parks and playgrounds.
3. Essential services are permitted except those that exceed sixty (60) feet in height or greater than one hundred fifteen (115) kilovolts.

1105.08 SUBD. 3. ACCESSORY USES.

The following are permitted accessory uses within the R-7 Zoning District.

1. Private garages, parking spaces and accessory structures for licensed and operable passenger cars and not more than one truck in excess of a gross vehicle weight rating of nine thousand (9,000) pounds. Private garages are intended for use to store the private passenger vehicles of the family or family's resident upon the premises, and in which no business service or industry is carried on.
2. Storage of recreational vehicles and equipment.
3. Home occupations as regulated by Section 1107.16 of this Ordinance.
4. Non-commercial greenhouses and conservatories.
5. Swimming pools, decks, tennis courts and other recreational facilities which are operated for the enjoyment and convenience of the residents of the principal use and their guests.
6. Tool houses, sheds and similar buildings for storage of domestic supplies and non-commercial recreational equipment.

(Ord. 18-01 Section 1105.08, Adopted February 20, 2018.)

1105.08 SUBD. 4. CONDITIONAL USES.

The following are conditional uses in an R-7 District requiring a conditional use permit based upon procedures set forth in and regulated by Sections 1103.08 and 1106.01 of this Ordinance.

1. Governmental and public regulated utility buildings and structures necessary for the health, safety and general welfare of the City.
2. Public or semi-public recreational buildings and neighborhood or community centers; public and private educational Institutions limited to elementary, junior high and senior high schools; hospitals and religious institutions such as churches, chapels, temples, synagogues and cemeteries.
3. Nursing homes and similar group housing.
4. Elderly (senior citizen) housing.
5. Reserved. (*Ord. 18-01 Section 1105.07, Adopted February 20, 2018.*)
6. Essential services exceeding sixty (60) feet in height or greater than one hundred fifteen (115) kilovolts.

1105.08 SUBD. 5. LOT REQUIREMENTS AND SETBACKS.

The following minimum requirements shall be observed in an R-7 District, subject to additional requirements, exceptions and modifications set forth in this Ordinance. Listed are minimum requirements, unless specifically identified as "maximum."

1. Lot Area: Ten thousand five hundred (10,500) square feet for up to four (4) units, plus two thousand (2,000) square feet for each additional unit.
2. Lot Width:
 - a. Interior: Seventy-five (75) feet.
 - b. Corner: One hundred (100) feet.
3. Setbacks: Principal Building:
 - a. Front Yard: Thirty (30) feet.
 - b. Side Yard:
 1. Interior Lot:
 - a. Single or two-family dwellings:
 - 1 Ten (10) feet.
 2. Zero (0) feet if the principal buildings share common walls.
 - b. All other uses:
 1. Equal to the height of the building.
 2. Corner Lot: Twenty (20) feet on the side yard abutting onto a public street.
 - c. Rear Yard:
 1. Twenty (20) feet or height of the building, whichever is greater.
 2. Zero (0) feet if the principal buildings share common walls.

-
4. Setbacks: Accessory Buildings:
 - a. Front Yard: Accessory buildings shall be located behind the front building line of the principal building and not less than thirty (30) feet from the front property line.
 - b. Side Yard:
 1. Interior Lot: Ten (10) feet.
 2. Corner Lot: Twenty (20) feet on the side yard abutting onto a public street.
 - c. Rear Yard:
 1. Five (5) feet.
 2. If entrance is fronting a public right-of-way: Twenty (20) feet.
 3. If Vehicle access to the structure is from an alley: fifteen (15) feet. (*Ord. 18-01 Section 1105.08, Adopted February 20, 2018.*)
 5. Site Coverage.
 - a. No structure or combination of structures, including detached garages, shall occupy more than sixty (60) percent of the lot area.
 6. Placement of Buildings.
 - a. There shall be a minimum of ten (10) feet between principal and accessory buildings (excluding decks).
 - b. There shall be no structures of any kind within any City easement, except if written permission has been granted by the City and the encroachment is in conformance with the City's Easement and Bluff Encroachment Requirements found in Chapter 12 of the City Code, Section 1205.07 Subd 4. EASEMENT AND BLUFF ENCROACHMENT REQUIREMENTS.

1105.08 SUBD. 6. BUILDING STANDARDS.

1. Maximum Height:
 - a. Principal Building: Thirty-five (35) feet.
 - b. Accessory Building: Fifteen (15) feet.
2. Floor Area:
 - a. Principal Building – Two-Family.
 1. Minimum:
 - a. One Bedroom: seven hundred fifty (750) square feet.
 - b. Two Bedrooms: nine hundred sixty (960) square feet.
 - c. Three plus Bedrooms: one thousand forty (1,040) square feet.
 - b. Principal Building – Multi-Family.
 1. Minimum:
 - a. One Bedroom: seven hundred fifty (750) square feet.
 - b. Two Bedrooms: nine hundred sixty (960) square feet.

- c. Three plus Bedrooms: one thousand forty (1,040) square feet.
 - c. Garages.
 - 1. Minimum - attached: four hundred (400) square feet (new construction).
 - 2. Maximum – detached:
 - a. Multiple family must conform with site coverage requirement.
 - d. Accessory Building:
 - 1. Maximum: nine hundred (900) square feet.
3. Garage door height shall not exceed nine (9) feet.
4. Minimum Width and Depth:
All dwellings, including manufactured homes, shall have a depth of at least twenty (20) feet for at least fifty (50) percent of their width. All dwellings, including manufactured homes, shall have a width of least twenty (20) feet for at least fifty (50) percent of their depth.
5. Garage floor elevations shall be not less than eighteen (18) inches and not more than thirty-six (36) inches as measured from the top of the curb at the mid-point of the garage to the garage floor at the mid-point of the garage door opening. The minimum slope of the driveway shall be 2% and the maximum slope of the driveway shall be 10%. Exceptions to these standards may be approved by the Zoning Administrator, after consultation with the City or development engineer, for special circumstances such as an increased setback, site topography and flooding potential, provided that proper site and area drainage is maintained and the elevation of the structure is in keeping with the character of the area. (Ord. 05-09, Sect. 1105, Adopted Nov. 7, 2005).

(Ord. 05-09, Sect. 1105, Adopted Nov. 7, 2005).
(Ord. 11-03 Section 1105, Adopted May 16, 2011).
(Ord. 12-04, Sections 1105, Adopted September 17, 2012.)
(Ord. 18-01 Section 1105.08, Adopted February 20, 2018.)